6" height

FS OR-G-LY4

49.75" width

39.5" width

39.5" width

Lyra
10' x 10' Truss System
UV Printed



Panels LY1 and LY3:
Total Graphic Area: 40.5" w x 84.75"h
Finished Size: 39.5"w x 83.75"h

Panels LY2:
Total Graphic Area: 50.75"w x 91"h
Finished Size: 49.75"w x 90"h

Panels LY4:
Total Graphic Area: 95.5"w x 7"h
Finished Size: 94.5"w x 6"h

Template requires 1/2" bleed around the perimeter

FS = Graphic is front side mounted (3/4" w magnet is applied to the back of the panel)
BS = Graphic is back side mounted (3/4" w velcro is applied to the front of the panel)
Notching = 7/8" square that is cut into the appropriate location.
Hinging= 3/4" strip of material that is cropped from the panel and reapplied with hinge tape. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 100-120ppi
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

BS
OR-G-LY1

BS
OR-G-LY2

BS
OR-G-LY3

bleed area
trim line

gray area will be obstructed once finished and mounted

Lyra
10′ x 10′ Truss System
UV Printed



Panels LY1 and LY3:
Total Graphic Area: 40.5″ w x 84.75″h
Finished Size: 39.5″w x 83.75″h

Panels LY2:
Total Graphic Area: 50.75″w x 91″h
Finished Size: 49.75″w x 90″h

Panels LY4:
Total Graphic Area: 95.5″w x 7″h
Finished Size: 94.5″w x 6″h

Template requires 1/2″ bleed around the perimeter

FS = Graphic is front side mounted (3/4″ w magnet is applied to the back of the panel)
BS = Graphic is back side mounted (3/4″ w velcro is applied to the front of the panel)
Notching = 7/8″ square that is cut into the appropriate location.
Hinging= 3/4″ strip of material that is cropped from the panel and reapplied with hinge tape. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

– CMYK Color Mode
– All Solid Coated Pantone colors should be called out in the art as spot colors
– Embed all images and support files
– Resolution must be 100-120ppi
– All fonts must be created to outlines
– Do not scale artboard
– Background color/images must bleed to the edge of artboard
– Do not use spot colors from template in your artwork as they will not print

BS

OR-G-LY1

bleed area
trim line

BS

OR-G-LY2

BS

OR-G-LY3

gray area will
be obstructed
once finished
and mounted

FS OR-G-LY4